


ITECH Z

ONE FITTING - MANY APPLICATIONS




» visibility up to 30 meters




- » plug-in connection – when the fitting is opened, the voltage on its active elements is cut off
- » high protection degree – IP65
- » ability to operate in low-temperature environments thanks to the COLD version
- » moulded high-resilience polyurethane gasket
- » one-sided or double-sided view fitting


44

Dimensions [± 2mm]




Application	evacuation road direction (evacuation sign)
Light source	LED 
Type	double-sided fitting
Testing for self-contained	non-addressable: ST – for bottom test non-addressable: AT – auto-test / self-test addressable: DATA – with addressable module for DATA system addressable: DALI – with addressable module for DALI systems
Testing for central battery	non-addressable: CB1 – without addressable module addressable: CB3 – with addressable module
Power supply	210÷250 V AC 50÷60 Hz 186÷254 V DC
Protection degree	IP65
Insulation class	II
Temperature range	ST, AT, DATA, DALI: $t_a +10^{\circ}\text{C} \div +40^{\circ}\text{C}$ CB1: $t_a -25^{\circ}\text{C} \div +55^{\circ}\text{C}$ CB3: $t_a -15^{\circ}\text{C} \div +40^{\circ}\text{C}$ COLD: $t_a -15^{\circ}\text{C} \div +40^{\circ}\text{C}$
Glow wire test	850°C
Colour	<input type="checkbox"/> RAL 9003 <input type="checkbox"/> RAL 7035 <input type="checkbox"/> RAL 9004 <input type="checkbox"/> special color
Material	housing: PC/ABS

» surface mounted




» TM-AKC.IT003

set for recessed mounting



Pictograms in the set:



Model	Mode	Time	Battery	Testing
iTECH Z E2 ECO	M / NM	3 h	LiFePO4	ST / AT / DATA / DALI
iTECH Z E2 PRO	M / NM	3 h	LiFePO4	ST / AT / DATA / DALI
iTECH Z E2 ECO	-	-	-	CB1, CB3
iTECH Z E2 PRO	-	-	-	CB1, CB3

For pictogram luminance > 500 cd/m² is necessary to order a special extension kit [IT +500 cd].

