



Module LLE 20x280-560mm 650lm LV SNC3

Modules LLE essence

Product description

- Optimal solution for linear and panel lights where cost is main priority, together with the new LC Ip SNC and ADV LED Driver provides best system efficiency
- 4 terminals for parallel wiring
- Perfectly uniform light, even if several LED modules are used together in a line
- Push terminals for quick and simple wiring of LED module to LED module
- Long life-time: 72,000 hours
- 5-year guarantee

Optical properties

- Colour temperatures 3,000 K, 4,000 K and 6,500 K
- Typ. luminous flux 650 and 1,300 lm
- Efficacy of the module up to 169 lm/W
- High colour rendering index CRI > 80
- Small colour tolerance MacAdam 3rd
- Small luminous flux tolerances

Mechanical properties

- Module dimension 20 x 280 mm and 20 x 560 mm
- Simple installation (e.g. screws)



LLE 20x280mm 650lm LV SNC3




LLE 20x560mm 1300lm LV SNC3



Standards, page 9

Colour temperatures and tolerances, page 13







Module LLE 20x280-560mm 650lm LV SNC3
Modules LLE essence

Technical data

Beam characteristic	120°
Ambient temperature range	-40 ... +65 °C
tp rated	50 °C
tc	90 °C
Irated for 650 lm	100 mA
Irated for 1,300 lm	200 mA
I _{max} for 650 lm	180 mA
I _{max} for 1,300 lm	360 mA
Max. permissible LF current ripple for 650 lm	200 mA
Max. permissible LF current ripple for 1,300 lm	400 mA
Max. permissible peak current for 650 lm	300 mA / max. 10 ms
Max. permissible peak current for 1,300 lm	600 mA / max. 10 ms
Max. working voltage for insulation SELV [®]	60 V
Insulation test voltage	0.5 kV
CTI of the printed circuit board	≥ 600
ESD classification	severity level 2
Risk group (IEC 62471:2008) [®]	RG1
Classification acc. to IEC 62031	Built-in
Type of protection	IP00
Life-time	up to 72,000 h



LLE 20x280mm 650lm LV SNC3



LLE 20x560mm 1300lm LV SNC3

Ordering data

Type	Article number	Colour temperature	Packaging carton	Weight per pc.
LLE 20x280mm 650lm 830 LV SNC3	28002925	3,000 K	180 pc(s).	0.018 kg
LLE 20x280mm 650lm 840 LV SNC3	28002926	4,000 K	180 pc(s).	0.018 kg
LLE 20x280mm 650lm 865 LV SNC3	28002927	6,500 K	180 pc(s).	0.018 kg
LLE 20x560mm 1300lm 830 LV SNC3	28002928	3,000 K	180 pc(s).	0.036 kg
LLE 20x560mm 1300lm 840 LV SNC3	28002929	4,000 K	180 pc(s).	0.036 kg
LLE 20x560mm 1300lm 865 LV SNC3	28002931	6,500 K	180 pc(s).	0.036 kg

Specific technical data

Type [®]	Photo-metric code	Typ. luminous flux at tp = 25 °C [®]	Typ. luminous flux at tp = 50 °C [®]	Typ. forward current	Min. forward voltage at tp = 50 °C	Max. forward voltage at tp = 25 °C	Typ. power consumption at tp = 50 °C [®]	Efficacy of the module at tp = 25 °C	Efficacy of the module at tp = 50 °C	Efficacy of the system at tp = 50 °C	Colour rendering index CRI
Operating mode NM at 100 mA per foot (280 mm module length)											
LLE 20x280mm 650lm 830 LV SNC3	830/359	550 lm	520 lm	100 mA	31.3 V	36.9 V	3.4 W	160 lm/W	154 lm/W	134 lm/W	> 80
LLE 20x280mm 650lm 840 LV SNC3	840/359	580 lm	550 lm	100 mA	31.3 V	36.9 V	3.4 W	169 lm/W	163 lm/W	147 lm/W	> 80
LLE 20x280mm 650lm 865 LV SNC3	865/359	580 lm	550 lm	100 mA	31.3 V	36.9 V	3.4 W	169 lm/W	163 lm/W	147 lm/W	> 80
LLE 20x560mm 1300lm 830 LV SNC3	830/359	1,110 lm	1,050 lm	200 mA	31.3 V	36.9 V	6.8 W	162 lm/W	155 lm/W	140 lm/W	> 80
LLE 20x560mm 1300lm 840 LV SNC3	840/359	1,160 lm	1,100 lm	200 mA	31.3 V	36.9 V	6.8 W	169 lm/W	163 lm/W	147 lm/W	> 80
LLE 20x560mm 1300lm 865 LV SNC3	865/359	1,160 lm	1,100 lm	200 mA	31.3 V	36.9 V	6.8 W	169 lm/W	163 lm/W	147 lm/W	> 80
Operating mode HO at 125 mA per foot (280 mm module length)											
LLE 20x280mm 650lm 830 LV SNC3	830/359	680 lm	640 lm	125 mA	31.9 V	37.6 V	4.3 W	155 lm/W	149 lm/W	134 lm/W	> 80
LLE 20x280mm 650lm 840 LV SNC3	840/359	710 lm	680 lm	125 mA	31.9 V	37.6 V	4.3 W	162 lm/W	158 lm/W	142 lm/W	> 80
LLE 20x280mm 650lm 865 LV SNC3	865/359	710 lm	680 lm	125 mA	31.9 V	37.6 V	4.3 W	162 lm/W	158 lm/W	142 lm/W	> 80
LLE 20x560mm 1300lm 830 LV SNC3	830/359	1,360 lm	1,290 lm	250 mA	31.9 V	37.6 V	8.6 W	155 lm/W	150 lm/W	135 lm/W	> 80
LLE 20x560mm 1300lm 840 LV SNC3	840/359	1,430 lm	1,360 lm	250 mA	31.9 V	37.6 V	8.6 W	163 lm/W	158 lm/W	142 lm/W	> 80
LLE 20x560mm 1300lm 865 LV SNC3	865/359	1,430 lm	1,360 lm	250 mA	31.9 V	37.6 V	8.6 W	163 lm/W	158 lm/W	142 lm/W	> 80
Operating mode HO at 150 mA per foot (280 mm module length)											
LLE 20x280mm 650lm 830 LV SNC3	830/359	800 lm	760 lm	150 mA	32.6 V	38.4 V	5.3 W	149 lm/W	144 lm/W	130 lm/W	> 80
LLE 20x280mm 650lm 840 LV SNC3	840/359	840 lm	800 lm	150 mA	32.6 V	38.4 V	5.3 W	157 lm/W	152 lm/W	137 lm/W	> 80
LLE 20x280mm 650lm 865 LV SNC3	865/359	840 lm	800 lm	150 mA	32.6 V	38.4 V	5.3 W	157 lm/W	152 lm/W	137 lm/W	> 80
LLE 20x560mm 1300lm 830 LV SNC3	830/359	1,610 lm	1,520 lm	300 mA	32.6 V	38.4 V	10.6 W	150 lm/W	144 lm/W	130 lm/W	> 80
LLE 20x560mm 1300lm 840 LV SNC3	840/359	1,690 lm	1,600 lm	300 mA	32.6 V	38.4 V	10.6 W	158 lm/W	152 lm/W	137 lm/W	> 80
LLE 20x560mm 1300lm 865 LV SNC3	865/359	1,690 lm	1,600 lm	300 mA	32.6 V	38.4 V	10.6 W	158 lm/W	152 lm/W	137 lm/W	> 80
Operating mode HO at 175 mA per foot (280 mm module length)											
LLE 20x280mm 650lm 830 LV SNC3	830/359	920 lm	870 lm	175 mA	33.3 V	39.2 V	6.3 W	144 lm/W	138 lm/W	124 lm/W	> 80
LLE 20x280mm 650lm 840 LV SNC3	840/359	970 lm	920 lm	175 mA	33.3 V	39.2 V	6.3 W	152 lm/W	146 lm/W	131 lm/W	> 80
LLE 20x280mm 650lm 865 LV SNC3	865/359	970 lm	920 lm	175 mA	33.3 V	39.2 V	6.3 W	152 lm/W	146 lm/W	131 lm/W	> 80
LLE 20x560mm 1300lm 830 LV SNC3	830/359	1,850 lm	1,750 lm	350 mA	33.3 V	39.2 V	12.6 W	145 lm/W	139 lm/W	125 lm/W	> 80
LLE 20x560mm 1300lm 840 LV SNC3	840/359	1,940 lm	1,840 lm	350 mA	33.3 V	39.2 V	12.6 W	152 lm/W	146 lm/W	131 lm/W	> 80
LLE 20x560mm 1300lm 865 LV SNC3	865/359	1,940 lm	1,840 lm	350 mA	33.3 V	39.2 V	12.6 W	152 lm/W	146 lm/W	131 lm/W	> 80

[®] Integral measurement over the complete module.

[®] If mounted with M4 screws and plastic washers.


[®] Measured at operating mode HO.

[®] HE ... high efficiency, NM ... nominal mode, HO ... high output.

[®] Tolerance range for optical and electrical data: ±10 %.

Product description

- LINEAR COVER for LLE 20
- Protection against direct touch for non-SELV applications
(recommendation: use all fixing points and screwed Endcap)
- Fast snap on mounting on to LLE 20 with M4 screws and plastic washers
- High transmission: transparent 94 %, semi-transparent 87 %, diffuse 76 %
- Made of PMMA
- Tolerances: ± 1 mm for 597 mm length (ends finished),
+ 20 mm for 1,200 / 1,500 / 1,600 / 1,800 mm length (ends raw)



Ordering data

Type	Article number	Colour	Length	Packaging carton	Weight per pc.
LINEAR COVER SY Transparent 1600mm	28000338	Transparent	1,600 mm	12 pc(s).	0.272 kg
LINEAR COVER SY Frosted 1800mm	28000437	Semi-transparent	1,800 mm	12 pc(s).	0.308 kg
LINEAR COVER SY Frosted 1600mm	28000339	Semi-transparent	1,600 mm	12 pc(s).	0.272 kg
LINEAR COVER SY Frosted 1500mm	28000435	Semi-transparent	1,500 mm	12 pc(s).	0.244 kg
LINEAR COVER SY Frosted 1200mm	28000422	Semi-transparent	1,200 mm	12 pc(s).	0.205 kg
LINEAR COVER SY Frosted 597mm	28000340	Semi-transparent	597 mm	12 pc(s).	0.102 kg
LINEAR COVER SY Diffuse 1800mm	28000438	Diffuse	1,800 mm	12 pc(s).	0.308 kg
LINEAR COVER SY Diffuse 1600mm	28000341	Diffuse	1,600 mm	12 pc(s).	0.272 kg
LINEAR COVER SY Diffuse 1500mm	28000436	Diffuse	1,500 mm	12 pc(s).	0.257 kg
LINEAR COVER SY Diffuse 1200mm	28000434	Diffuse	1,200 mm	12 pc(s).	0.205 kg
LINEAR COVER SY Diffuse 597mm	28000342	Diffuse	597 mm	12 pc(s).	0.102 kg

Product description


- ENDCAP for LLE 20
- PUSH-FIX: Fast snap on mounting (sheet thickness 0.5 – 1.0 mm), for drilling hole 4 mm
- SCREW-FIX: Screw mounting with EJOT Delta PT WN 5451 30x8, tightening torque 0.7 Nm
- Made of Polycarbonat




ACL ENDCAP LLE24 PUSH-FIX



ACL ENDCAP LLE24 SCREW-FIX



ACL ENDCAP LLE24 PUSH-FIX



ACL ENDCAP LLE24 SCREW-FIX

Ordering data

Type	Article number	Colour	Packaging carton	Weight per pc.
ACL ENDCAP LLE24 PUSH-FIX	28001037	White	480 pc(s).	0.003 kg
ACL ENDCAP LLE24 SCREW-FIX	28002315	White	480 pc(s).	0.003 kg

Product description LINEAR LENS

- Linear lens for LLE 20
- Available with different beam characteristics
- Protection against direct touch for non-SELV applications (recommendation: use all fixing points and screwed Endcap)
- Fast snap on mounting on to LLE 20 with M4 screws and plastic washers
- Linear lense made of PMMA
- Available lengths: 1,200, 1,500, 1,600 and 1,800 mm, Tolerance: + 10 mm, at 1,600 mm length ± 20 mm tolerance and raw ends
- Max. permissible temperature 80 °C
- Photometric data available on website

Product description Endcap

- ENDCAP for LINEAR LENS 24mm INTENSE, ASY and DASY
- Mounting by clipping in and screwing from below using screw EJOT Delta PT WN 5451 20x4, tightening torque 0.7 Nm
- Made of Polyamide UL94 V0



ACL LINEAR LENS 24mm 60°



ACL LINEAR LENS 24mm 90°



ACL LINEAR LENS 24mm INTENSE



ACL LINEAR LENS 24mm ASY




ACL LINEAR LENS 24mm DASY




ACL Endcap LENS 24mm PSF


ACL LENS 24mm




ACL LINEAR LENS 24mm 60° and 90°



ACL LINEAR LENS 24mm INTENSE




ACL LINEAR LENS 24mm ASY



ACL LINEAR LENS 24mm DASY

ACL LENS 24mm



ACL Endcap LENS 24mm PSF

Ordering data

Type	Article number	Beam characteristic	Efficiency	Packaging carton	Weight per pc.
ACL LINEAR LENS 24x1200mm 60°	28001428	60°	97 %	21 pc(s).	0.196 kg
ACL LINEAR LENS 24x1200mm 90°	28001429	90°	97 %	21 pc(s).	0.165 kg
ACL LINEAR LENS 24x1600mm 60°	28000953	60°	97 %	21 pc(s).	0.261 kg
ACL LINEAR LENS 24x1600mm 90°	28000955	90°	97 %	21 pc(s).	0.221 kg
ACL LINEAR LENS 24x1200mm INTENSE	28002024	40°	95 %	18 pc(s).	0.261 kg
ACL LINEAR LENS 24x1500mm INTENSE	28002025	40°	95 %	18 pc(s).	0.326 kg
ACL LINEAR LENS 24x1800mm INTENSE	28002026	40°	95 %	18 pc(s).	0.392 kg
ACL LINEAR LENS 24x1200mm ASY	28002030	asymmetric	95 %	18 pc(s).	0.250 kg
ACL LINEAR LENS 24x1500mm ASY	28002031	asymmetric	95 %	18 pc(s).	0.312 kg
ACL LINEAR LENS 24x1800mm ASY	28002032	asymmetric	95 %	18 pc(s).	0.375 kg
ACL LINEAR LENS 24x1200mm DASY	28002033	double asymmetric	92 %	18 pc(s).	0.249 kg
ACL LINEAR LENS 24x1500mm DASY	28002034	double asymmetric	92 %	18 pc(s).	0.311 kg
ACL LINEAR LENS 24x1800mm DASY	28002035	double asymmetric	92 %	18 pc(s).	0.373 kg
ACL Endcap LENS 24mm PSF	28002669	–	–	720 pc(s).	0.003 kg

1. Standards

IEC 62031
IEC 62471
IEC 61000-4-2
IEC 62778
IEC 61547

1.1 Photometric code

Key for photometric code, e. g. 830 / 349

1 st digit	2 nd + 3 rd digit	4 th digit	5 th digit	6 th digit
Code	CRI	Colour temperature in Kelvin x 100	MacAdam initial	MacAdam after 25% of the life-time (max.6000h)
7	70 – 79			Luminous flux after 25% of the life-time (max.6000h)
8	80 – 89			Code
9	≥90			Luminous flux
				7 ≥ 70 %
				8 ≥ 80 %
				9 ≥ 90 %

1.2 Energy classification

Type	Energy classification
LLE 20mm LV SNC3	A++

2. Thermal details

2.1 tc point, ambient temperature and life-time

The temperature at tp reference point is crucial for the light output and life-time of a LED product.

For LLE a tp temperature of 50 °C has to be complied in order to achieve an optimum between heat sink requirements, light output and life-time.

Compliance with the maximum permissible reference temperature at the tc point must be checked under operating conditions in a thermally stable state. The maximum value must be determined under worst-case conditions for the relevant application.

The tc and tp temperature of LED modules from Tridonic are measured at the same reference point.

2.2 Storage and humidity

Storage temperature	-40 ... +85 °C
---------------------	----------------

Operation only in non condensing environment.
Humidity during processing of the module should be between 30 to 70 %.

2.3 Heat sink values

LLE 24x280mm 650lm 8xx LV SNC3

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	50 °C	75 mA		self cooling
25 °C	50 °C	100 mA		self cooling
25 °C	50 °C	150 mA	8.48 K/W	79 cm²
35 °C	50 °C	75 mA		self cooling
35 °C	50 °C	100 mA	8.44 K/W	79 cm²
35 °C	50 °C	150 mA	5.09 K/W	131 cm²
40 °C	50 °C	75 mA	7.96 K/W	84 cm²
40 °C	50 °C	100 mA	5.62 K/W	119 cm²
40 °C	50 °C	150 mA	3.39 K/W	197 cm²
45 °C	50 °C	75 mA	3.98 K/W	168 cm²
45 °C	50 °C	100 mA	2.81 K/W	238 cm²
45 °C	50 °C	150 mA	1.69 K/W	394 cm²

LLE 24x560mm 1300lm 8xx LV SNC3

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	50 °C	150 mA		self cooling
25 °C	50 °C	200 mA		self cooling
25 °C	50 °C	300 mA	4.21 K/W	158 cm²
35 °C	50 °C	150 mA		self cooling
35 °C	50 °C	200 mA	4.18 K/W	160 cm²
35 °C	50 °C	300 mA	2.52 K/W	264 cm²
40 °C	50 °C	150 mA	4.00 K/W	167 cm²
40 °C	50 °C	200 mA	2.78 K/W	239 cm²
40 °C	50 °C	300 mA	1.68 K/W	396 cm²
45 °C	50 °C	150 mA	2.00 K/W	334 cm²
45 °C	50 °C	200 mA	1.39 K/W	480 cm²
45 °C	50 °C	300 mA	0.84 K/W	795 cm²

Notes

The actual cooling surface can differ because of the material, the structural shape, outside influences and the installation situation. Depending on the heat sink a heat conducting paste or heat conducting film might be necessary to keep the specified tp temperature.

3. Installation / wiring

3.1 Electrical supply/choice of LED Driver

LLE modules from Tridonic are not protected against overvoltages, overcurrents, overloads or short-circuit currents. Safe and reliable operation can only be guaranteed in conjunction with a LED Driver which complies with the relevant standards. The use of LED Driver from Tridonic in combination with LLE modules guarantees the necessary protection for safe and reliable operation.

If a LED Driver other than Tridonic is used, it must provide the following protection:

- Short-circuit protection
- Overload protection
- Overtemperature protection



LLE modules must be supplied by a constant current LED Driver. Operation with a constant voltage LED Driver will lead to an irreversible damage of the module.

Wrong polarity can damage the LLE.

With parallel wiring tolerance-related differences in output are possible (thermal stress of the module) and can cause differences in brightness.

If a wire breaks or a complete module fails then the current passing through the other module increases. This may reduce its life considerably.


The max. permissible output current of the LED Driver for parallel wiring is 3 A.

LLE have to be operated with SELV LED Drivers.





LLE are basic insulated up to 60 V SELV (if mounted with M4 screws with head diameter 7 mm in combination with plastic washers) against ground and can be mounted directly on earthed metal parts of the luminaire. If the max. output voltage of the LED Driver (also against earth) is above 60 V SELV, an additional insulation between LED module and heat sink is required (for example by insulated thermal pads) or by a suitable luminaire construction.

3.2 Wiring



Wiring examples




Type	Max. number with parallel wiring*
LLE 20x280mm 650lm LV SNC3	8
LLE 20x560mm 1300lm LV SNC3	4

* with direkt chaining (without additional terminals).

3.3 Wiring type and cross section

The wiring can be in stranded wires or solid with a cross section of 0.2 to 0.75 mm².

For the push-wire connection you have to strip the insulation (8–9 mm).



To remove the wires use a suitable tool (e.g. Microcon release pin) or through twist and pull.

3.4 Mounting instruction



None of the components of the LLE (substrate, LED, electronic components etc.) may be exposed to tensile or compressive stresses.

Max. torque for fixing: 0.5 Nm.

The LED modules are mounted onto a heat sink with min. 3 screws per module.



Chemical substance may harm the LED module. Chemical reactions could lead to colour shift, reduced luminous flux or a total failure of the module caused by corrosion of electrical connections.

Materials which are used in LED applications (e.g. sealings, adhesives) must not produce dissolver gas. They must not be condensation curing based, acetate curing based or contain sulfur, chlorine or phthalate.

Avoid corrosive atmosphere during usage and storage.

3.5 EOS/ESD safety guidelines



The device / module contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken. No special measures need to be taken for devices/modules with enclosed casings (contact with the pc board not possible), just normal installation practice. Please note the requirements set out in the document EOS / ESD guidelines (Guideline_EOS_ESD.pdf) at: <http://www.tridonic.com/esd-protection>

4. Life-time

4.1 Life-time, lumen maintenance and failure rate

The light output of an LED Module decreases over the life-time, this is characterized with the L value.
L70 means that the LED module will give 70 % of its initial luminous flux.
This value is always related to the number of operation hours and therefore defines the life-time of an LED module.

As the L value is a statistical value and the lumen maintenance may vary over the delivered LED modules.
The B value defines the amount of modules which are below the specific L value, e.g. L70B10 means 10 % of the LED modules are below 70 % of the initial luminous flux, respectively 90 % will be above 70 % of the initial value.
In addition the percentage of failed modules (fatal failure) is characterized by the C value.

The F value is the combination of the B and C value. That means for F degradation and complete failures are considered, e.g. L70F10 means 10 % of the LED modules may fail or be below 70 % of the initial luminous flux.

4.2 Lumen maintenance for LLE 20mm LV SNC3

Forward current	tp						
	tempera- ture	L90 / F10	L90 / F50	L80 / F10	L80 / F50	L70 / F10	L70 / F50
100 mA / ft	40 °C	68,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
(280 mm module length)	50 °C	60,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h

4.3 Switching capability

100,000 cycles

Tridonic test according to IEC 62717 Cl 10.3.3
30 s on / 30 s off at Imax

5. Electrical values

5.1 Declaration of electrical parameters

I_{rated} ... Nominal operating current the module is designed for.


I_{max} ... Max. permissible continuous operating current incl. The tolerances of the LED driver.

Max. permissible LF current ripple ... Max. output current of the LED driver incl. Tolerances and LF current ripple must not exceed this value.


Max. permissible peak current ... The max. output peak current of the LED driver must not exceed this value.

5.2 Typ. forward voltage vs. forward current


LLE 20x280mm 650lm 8xx LV SNC3



LLE 20x560mm 1300lm 8xx LV SNC3



5.3 Forward voltage vs. tc temperature



The diagrams are based on statistic values.
The real values can be different.

6. Photometric characteristics

6.1 Coordinates and tolerances according to CIE 1931


The specified colour coordinates are integral measured by current impulse of 195 mA and a duration of 100 ms.

The ambient temperature of the measurement is $t_a = 25^\circ\text{C}$.


The measurement tolerance of the colour coordinates are ± 0.01 .

3,000 K

	x0	y0
Centre	0.4354	0.4009




— MacAdam Ellipse: 3SDCM




4,000 K

	x0	y0
Center	0.3830	0.3771




— MacAdam Ellipse: 3SDCM




6,500 K

	x0	y0
Center	0.3129	0.3261




— MacAdam Ellipse: 3SDCM



6.2 Light distribution


The optical design of the LLE product line ensures optimum homogeneity for the light distribution.



The colour temperature is measured integral over the complete module. The single LED light points can have deviations in the colour coordinates within MacAdam 5.


To ensure an ideal mixture of colours and a homogeneous light distribution a suitable optic (e. g. PMMA diffuser) and a sufficient spacing between module and optic (typ. 4 cm) should be used.

6.3 Relative luminous flux vs. tc temperature




6.4 Relative luminous flux vs. operating current

LLE 20x280mm 650lm 8xx LV SNC3



LLE 20x560mm 1300lm 8xx LV SNC3



The diagrams are based on statistic values.
The real values can be different.

7. Miscellaneous

7.1 Additional information

Additional technical information at www.tridonic.com → Technical Data

Guarantee conditions at www.tridonic.com → Services

Life-time declarations are informative and represent no warranty claim.